

Washington County Fair 2011

TRUCK CLASS RULES

1. Any Standard Truck, Suburban, Blazer, Bronco type vehicles are allowed. If you are in question please call first.
2. Any fiberglass roofs or shells must be removed and car stripping rules will apply.
3. You may replace the dash with a spreader bar not to exceed 4" in diameter and a bar behind the seat or at the front of the bed is mandatory. End plates may be 6" in diameter. Bars in the bed may not be placed more than 2 ½ feet behind the cab.
4. A full roll bar or vertical bar from the rear bar to the roof should be installed. Bars near the head must be padded.
5. Driver's door and door posts near the driver must be padded.
6. A door bar may be placed on the exterior of the driver's door.
7. All door and hood seams must be welded. Side window openings at the bottom of the window may be welded.
8. Beds must be welded to the cab.
9. A 6 gallon (max) fuel cell or metal gas tank must be mounted at the front of the bed. A spreader bar with end plates should be welded in near the tank at the front of the bed to protect the tank. Tank should be covered to prevent gas from splashing in case of rupture.
10. A secure net is mandatory for the back window of single cab trucks to prevent whiplash.
11. All tail gates must be fully welded.
12. Only two wheel drive may be functioning.
13. Any OEM style car or truck bumper may be used. If truck has a beam type bumper it may not be welded to the body. You may weld a "tin" type bumper to the body. (call if you have questions)
14. No inner seam welding or body mount replacing for the exception of the core support mounts and 2 mounts in the bed. They may be replaced with 1" all-thread and may pass through the frame, body, and the hood where applicable.
15. Any engine/transmission combination may be used as long as they are within 4" of the stock motor. No motor mounts may be used to strengthen the frame. Car distributor protection and front engine protection rules apply.
16. Bumpers may be welded directly to the frame. Bumper brackets may be used also. No frame seam welding is allowed. Bumpers must be secured to the frame with weld and/or secured to the body using 2 pieces of strap not to exceed 3" in width and 3/8" in thickness. If the rear bumper is removed, the tailgate must be lowered and secured to the frame and body.
17. Only 10 leaves in the front and 12 leaves in the back will be allowed under the truck if building leaf packs. 3" steps between leaves are required. Only 3 clamps may

- be used per leaf pack. There will be some exception to this rule if leaf packs are 100% stock. Only $\frac{3}{4}$ ton truck suspensions or smaller will be allowed.
18. One or two bars should be installed in the front window from the cowl area to the roof.
 19. No bed wedging, or suburban "sedagoning" allowed. Call if you have questions.
 20. All ends of frame rails must be covered. No exposed frame rails will be allowed.

Entry fee: \$50 Make check payable to "Brent Gafa"
Send to Brent Gafa
3479 S 1100 W
Hurricane, UT 84737

Contact:
Brent Gafa: (435)-669-3589
Matt Wetzel: (435)-467-3999