

Washington County Fair 2016-Figure 8 Class Car Rules

August 13th

1. Wheelbase 112 inches or less (center to center) No Bigger than a 6 cylinder engine.
2. All glass, exterior metal chrome strips, lettering, chrome fasteners, door handles, etc., must be removed from the car. (Do not leave broken glass in door.)
3. Doors, hoods, and trunks of the car must be welded or chained closed.
4. Rear seat must be removed. Seat belt is mandatory, and must be securely fastened to the car.
5. Factory installed seat belts are preferred.
6. All flammable materials, plastic items, non-essentials (loose tools, etc.) Items must be removed from vehicle prior to inspection. We will not inspect your car until your cars are cleaned.
7. All glass or plastic on dashboard must be removed or taped over.
8. Driver's side door and post must be padded.
9. Driver's side can be reinforced and roll over protection is (Recommended.) Roll over protection is mandatory on all hard tops. (Cars with no B pillar)
10. Gas tank (5 Gallon MAX) can be put in the rear seat area of the car and fastened securely. Factory tank will be allowed, if in front of the rear axle.
11. Radiators must remain in stock position, water only!
12. Cutting Fenders for tire clearance is allowed.
13. Only the driver will be permitted to race, full face crash helmet will be required
14. Drivers must remain in the vehicle at all times during competition. If you jump out of your car for any reason other than fire you will be disqualified.
15. A driver under the age of 18 must have a release form signed by parent or legal guardian. This must be signed in front of the officials.
16. No intentional driver side door hits.
17. No Alcohol in the Pit area.
18. If your car catches on fire more than twice you will hold position but will not be permitted to continue racing in the heat.
19. Homemade bumpers cannot extend past the center of the tires when pointed straight. Homemade bumpers must be flat with no point. Bumpers may only be mounted to the frame rails and have a single kicker bar running from the bumper to the shock tower. This kicker may be no larger than 2" x 2" square or 2" round tube. You may also add a push bar to the top of the bumper. It may not extend more than 2" above the front most portion of the hood.

Judges decisions are final.

Due to the various builds we will be running with two classes. If it is built outside of the above rules it will run in the heavy class. We will be running a heavy class and a light class.